HELVEMED S.A.

HELVEMED Instrument Forte+

Revision date: 01.09.2017 Revision No: 1,21

Product code: 20335352-0307

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

HELVEMED Instrument Forte+

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Instrument disinfectant

1.3. Details of the supplier of the safety data sheet

Company name: HELVEMED S.A.

Street: Route de Thonon 63

Place: CH-1222 Vésenaz/Genève

Responsible Department: Telephone number: +41 (0) 22 / 718 75 00

Telefax number: +41 (0) 22 / 718 75 05

E-Mail: info@helvemed.com Internet: www.helvemed.com

1.4. Emergency telephone number: INTERNATIONAL: +41 (0) 22 / 718 75 00 (24h - 7d/w - 365d/a)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture according to 1272/2008/EC

Hazard categories:

Flammable liquid: Flam. Liq. 3 Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Corr. 1B

Serious eye damage/eye irritation: Eye Dam. 1

Specific target organ toxicity - repeated exposure: STOT RE 1 Hazardous to the aquatic environment: Aquatic Acute 1 Hazardous to the aquatic environment: Aquatic Chronic 1

Hazard Statements:

Flammable liquid and vapour.

Harmful if swallowed.

Causes severe skin burns and eye damage.

Causes damage to organs through prolonged or repeated exposure.

Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazardous components which must be listed on the label

Fattyalcoholpolyglycolether Laurylpropylene diamine

Propan-1-ol

Signal word: Danger

Pictograms:



Hazard statements

H226 Flammable liquid and vapour.

GB - EN Page 1 of 9

HELVEMED S.A.

HELVEMED Instrument Forte+

Revision date: 01.09.2017 Revision No: 1,21

Product code: 20335352-0307

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H372 Causes damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe vapour.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P273 Avoid release to the environment.

P391 Collect spillage.

Additional advice on labelling

In accordance with section 1.5.2 of Annex I of the European Regulation (EC) No 1272/2008, following H and P statements may be omitted for containers < 125 ml: H226, H302, H410, P210, P273, P391

2.3. Other hazards

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Alkaline concentrate with alkylamines and non-ionic surfactants

Hazardous components

CAS No	Chemical name						
	EC No	Index No	REACH No				
	Classification according to Regulation (EC) No. 1272/2008 [CLP]						
127036-24-2	Fattyalcoholpolyglycolether						
	Acute Tox. 4, Eye Dam. 1; H302 H318						
5538-95-4	Laurylpropylene diamine						
	226-902-6						
	Acute Tox. 3, Skin Corr. 1B, STOT RE 1, Aquatic Acute 1 (M-Factor = 10), Aquatic Chronic 1; H301 H314 H372 H400 H410						
71-23-8	Propan-1-ol						
	200-746-9	603-003-00-0	01-2119486761-29				
	Flam. Liq. 2, Eye Dam. 1, STOT SE 3; H225 H318 H336						
	Reaction mixture of (2S)-alanine, N, N-bis (carboxymethyl) -, trisodium salt and (2R)-alanine, N, N-bis (carboxymethyl) -, trisodium salt in water						
			01-0000016977-53				
	Met. Corr. 1; H290						

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

If you feel unwell, seek medical advice.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.

GB - EN Page 2 of 9

HELVEMED S.A.

HELVEMED Instrument Forte+

Revision date: 01.09.2017 Revision No: 1,21

Product code: 20335352-0307

In the event of symptoms refer for medical treatment.

After contact with skin

Wash off immediately with soap and plenty of water.

Treat subsequently with skin cream.

Consult a physician.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids.

Summon a doctor immediately.

After ingestion

Induce vomiting only upon the advice of a physician.

Drink plenty of water.

Do not induce vomiting.

Summon a doctor immediately.

4.2. Most important symptoms and effects, both acute and delayed

Causes severe skin burns and eve damage.

Harmful if swallowed.

Causes damage to organs through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

Additional information

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

6.2. Environmental precautions

Do not discharge into surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

GB - EN Page 3 of 9

HELVEMED S.A.

HELVEMED Instrument Forte+

Revision date: 01.09.2017 Revision No: 1,21

Product code: 20335352-0307

Use only in thoroughly ventilated areas. Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Vapour/air mixture is explosive, even in empty uncleaned receptacles.

Do not smoke.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep containers tightly closed in a dry, well-ventilated place.

Advice on storage compatibility

Incompatible with strong acids and oxidizing agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Instrument disinfectant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
71-23-8	Propan-1-ol	200	500		TWA (8 h)	WEL
		250	625		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Protective gloves resistant to chemicals made off butyl, minimum coat thickness 0,7 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (EN 368).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: Blue green

Odour: Perfumed (scented)

GB - EN Page 4 of 9

HELVEMED S.A.

HELVEMED Instrument Forte+

Revision date: 01.09.2017 Revision No: 1,21

Product code: 20335352-0307

pH-Value (at 20 °C): approx. 10 Concentrate

Changes in the physical state

Initial boiling point and boiling range: > 89 °C

Flash point: 36 °C DIN 51755

Lower explosion limits: 2.1 vol. %

Upper explosion limits:

Ignition temperature: > 400 °C

Density (at 20 °C): 0,98 g/cm³

Water solubility: Miscible

(at 20 °C)

Solvent content: 5 - 15 %

9.2. Other information

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with acids and strong oxidizing agents.

10.4. Conditions to avoid

Vapour/air mixtures are explosive at intensive warming. Heating can release vapours which can be ignited.

10.5. Incompatible materials

Strong acids and oxidizing agents

10.6. Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Harmful if swallowed.

No toxicological data available.

ATEmix/oral: ~ 600 mg/kg

Irritation and corrosivity

Causes severe skin burns and eye damage. Causes severe skin burns and eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

Severe effects after repeated or prolonged exposure

Causes damage to organs through prolonged or repeated exposure. (Laurylpropylene diamine)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

GB - EN Page 5 of 9

HELVEMED S.A.

HELVEMED Instrument Forte+

Revision date: 01.09.2017 Revision No: 1,21

Product code: 20335352-0307

Practical experience

Other observations

Inhalation of vapours in high concentration can cause narcotic effects.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Very toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT substance.

12.6. Other adverse effects

Hazardous water pollutant.

Further information

Product is not allowed to be discharged into aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

070699

WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease, soaps,

detergents, disinfectants and cosmetics; wastes not otherwise specified

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 2920

14.2. UN proper shipping name: CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Laurylpropylene diamine,

Propan-1-ol)

14.3. Transport hazard class(es): 8

14.4. Packing group:

Hazard label: 8+3



Classification code:

GB - EN Page 6 of 9

HELVEMED S.A.

HELVEMED Instrument Forte+

Revision date: 01.09.2017 Revision No: 1,21

Product code: 20335352-0307

Tunnel restriction code:

Limited quantity: 1 L / 30 kg
Excepted quantity: E2
Transport category: 2
Hazard No: 83

Inland waterways transport (ADN)

14.1. UN number: UN 2920

14.2. UN proper shipping name: CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Laurylpropylene diamine,

Propan-1-ol)

D/E

14.3. Transport hazard class(es): 8
14.4. Packing group:

Hazard label: 8+3



Classification code: CF1

Limited quantity: 1 L / 30 kg

Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 2920

14.2. UN proper shipping name: CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Laurylpropylene diamine,

Propan-1-ol)

14.3. Transport hazard class(es): 8

14.4. Packing group:

Hazard label: 8+3



Marine pollutant:

Limited quantity:

Excepted quantity:

Yes

1 L / 30 kg

Excepted quantity:

E2

EmS: F-E. S-C

Air transport (ICAO)

14.1. UN number: UN 2920

14.2. UN proper shipping name: CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Laurylpropylene diamine,

Propan-1-ol, Solution)

14.3. Transport hazard class(es): 8

14.4. Packing group:

Hazard label: 8+3



Limited quantity Passenger: 0.5 L

Passenger LQ: Y840 Excepted quantity: E2

IATA-packing instructions - Passenger: 851
IATA-max. quantity - Passenger: 1 L
IATA-packing instructions - Cargo: 855
IATA-max. quantity - Cargo: 30 L

14.5. Environmental hazards

GB - EN Page 7 of 9

HELVEMED S.A.

HELVEMED Instrument Forte+

Revision date: 01.09.2017 Revision No: 1,21

Product code: 20335352-0307

ENVIRONMENTALLY HAZARDOUS: ves



14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): 5 - 15 %

Additional information

Regulation (EC) No 648/2004 (Regulation on detergents):

Non-ionic surfactants 15 - 30%, Parfum

Ingredients subject to the labelling obligation according to SCCP:

citronellol, Geraniol

National regulatory information

Employment restrictions: Observe employment restrictions for young people. Observe employment

restrictions for child bearing mothers and nursing.

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H290 May be corrosive to metals.

H301 Toxic if swallowed. H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

GB - EN Page 8 of 9

HELVEMED S.A.

HELVEMED Instrument Forte+

Revision date: 01.09.2017 Revision No: 1,21

Product code: 20335352-0307

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

GB - EN Page 9 of 9